

PRODUCT INFORMATION BULLETIN

FOR LAMINATION OF RIGID MULTILAYER, FLEXIBLE CIRCUITS AND UNCLAD LAMINATES



PACOTHANE® LE2000

OVERVIEW

PACOTHANE® LE2000 – is designated for those Pacothane release film applications that require a very low extraction of residues on the surface of the laminated substrate. “LE” is perfect for Unclad, Kapton and Stiffener builds which require pristine surfaces post lamination for further secondary sequential lamination builds or printing applications.

LAMINATION APPLICATIONS


- **Rigid Multilayer Panels:** to contain resin squeeze-out; to buffer and protect copper from damaged plates; to minimize stress effect from aluminum plates; to reduce frequency of plate cleaning; to increase plate life; to prevent press pads from sticking to plates or bonding to tooling pins. (See lay-up recommendation)
- **Flex, Rigid-Flex Panels:** to contain resin squeeze-out; for complete conformity to part topography; to provide easy separation of conformal hydraulics and driver pads from PCB surfaces. (See lay-up recommendation)

For both of the above applications “LE” creates a better surface quality on Copper Foil, Kapton and various Unclad Resins where optimum post lamination cleaning processes may not be available.

FEATURES

- Contaminate free release from resins and separator plates
- Rated for Operating Temperatures up to 400°F (204°C) for up to 2 Hours
- Optimal thickness at 1.8 mils (47µm) for easy Handling (50% thicker than competitive release films)
- No embedded impurities
- Extremely low X&Y Axis shrinkage with reduced static potential
- Essentially inert: no out-gassing, no plate residue, no inter-laminar adhesion influence, and no vacuum system contamination
- Environmentally friendly: no Ozone depleting chemicals, no fluorine's
- “LE” low extractable offers a cleaner surface free of residues with minimum extraction characteristics

RECOMMENDED LAMINATION LAY-UP



37 East Street, Winchester, MA 01890
Phone: 781-729-0927 Fax: 781-729-0929
email: sales@pacothane.com web: www.pacothane.com

PRODUCT INFORMATION BULLETIN

FOR LAMINATION OF RIGID MULTILAYER, FLEXIBLE CIRCUITS AND UNCLAD LAMINATES



PACOTHANE® LE2000

DESCRIPTION OF STANDARDS

Physical Property	Test Method		Reported Units	Typical Values	
Max. Application Temp.	Q 1025		°F (°C)	400(204)	
Thickness	Q 3019		mil (µm)	1.80 (47)	
Density	ASTM		g/cm3	0.94	
Heat Shrinkage	MD TD	Q-1045	%	<5%	
			%	<5%	
Melting Temp.	ASTM E794		°F (°C)	495°F (257°C)	
Appearance	White, Semi-translucent				
Tensile Strength (At yeild point)	MD	YP	ASTM D882	Kg/cm2	230
		Elong	ASTM D882	%	410
	TD	YP	ASTM D882	Kg/cm2	190
		Elong	ASTM D882	%	520

AVAILABILITY

PACOTHANE® LE2000 RELEASE FILM is available in rolls and in custom-made sheet sizes, tooled to customer specifications. The complete line of Pacothane products is available from leading local Distributors Worldwide who offer "Just in Time" delivery from locally-available stocks.

Also from Pacothane® Technologies:

RELEASE PRODUCTS



PRESS PADS



CONFORMABLES



CONTAMINATION CONTROL



ULTRA HIGH TEMPERATURE



Information contained in this technical literature is believed to be accurate and is offered in good faith for the benefit of the consumer. Inasmuch as Pacothane® Technologies has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any Pacothane® Technologies patent or application covering such use or as recommendations for use of such materials in the infringement of any patent.

D I S T R I B U T E D W O R L D W I D E .

REPRESENTED BY:

